



WKA PRE-TECH FORM

RACE CLASS	KART NUMBER	TRANSPONDER #
		Rental T _ _ _
		Personal

DRIVER NAME (PLEASE PRINT): _____ DATE : _____

DIRECTIONS: PLEASE INDICATE COMPLIANCE FOR EACH ITEM BY CHECKING THE CORRESPONDING BOX

THIS FORM MUST BE SUBMITTED TO THE TECH PRIOR TO ENTERING THE TRACK FOR ANY SESSION. FAILURE TO DO SO MAY RESULT IN A PENALTY ASSESSMENT AS DETERMINED BY THE RACE OFFICIALS.

ITEMS THAT NEED TO BE SECURED BY
NYLOCK AND SAFETY WIRE,
COTTER PIN, CIRCLIP OR SNAP RING

ITEMS THAT NEED TO BE
PRESENT AND FUNCTIONAL

STEERING ASSEMBLY

- ☐ STEERING WHEEL TO HUB BOLTS
- ☐ STEERING HUB TO SHAFT BOLTS
- ☐ STEERING SHAFT TO CHASSIS
- ☐ TIE ROD END BOLTS
- ☐ KINGPIN BOLTS
- ☐ SPINDLE NUT ATTACHING WHEEL

ENGINE AND DRIVETRAIN

- ☐ THROTTLE RETURN SPRING
- ☐ CLUTCH / CHAIN GUARD
- ☐ AIRBOX / MUFFLER
- ☐ THROTTLE CABLE
- ☐ HEADER BOLTS (SAFETY WIRED)
- ☐ ENGINE MOUNT BUTTERFLIES (CLAMPS)
- ☐ FUEL TANK / OIL OVERFLOW (NO LEAKS)
- ☐ TAG CLASSES TO HAVE BATTERY SECURED WITH A 175 LB PLASTIC CABLE TIE
- ☐ FOUR STROKE CLASSES TO HAVE EXHAUST PIPE WRAPPED

BRAKING SYSTEM

- ☐ PEDAL PIVOT TO CHASSIS
- ☐ ACTUATING ROD AND CABLE ENDS
- ☐ MASTER CYLINDER TO CHASSIS BOLTS
- ☐ CALIPER(S) TO CHASSIS BOLTS
- ☐ PAD RETAINING RODS
- ☐ BRAKE LOCKS WHEN ENGAGED
- ☐ BRAKE ROTOR TO HUB
(SAFETY WIRE OR METAL LOCKNUTS ONLY)

GENERAL SAFETY REQUIREMENTS

- ☐ WEIGHTS (BALLAST)
 - Weight(s) under 7 lbs must be secured by (1) 5/16 or 8mm bolt and must be double nutted.
 - Weight(s) from 7 to 15 lbs must be secured by (2) 5/16 or 8mm bolts and must be double nutted.
 - NO weights above 15 lbs will be permitted.
 - Each bolt location in the seat cannot exceed 15 lbs. per location.
 - Stacking of weights is allowed and must comply with above rules.
 - Weight(s) must be painted white with single a kart number clearly displayed and legible.
 - No weight can be attached to the nerf bars, the back bumper or plastic body work. No weight can be on the driver's body, safety gear or clothes.
 - All weights mounted to the seat must have a minimum of 1 1/4" OD fender style washer on the inside of the seat and another placed against the weight with the securing nuts. No washers or grommets between the seat and the weight. All weights must be tight.
- ☐ No cameras can be mounted on or inside a driver's helmet.
- ☐ Kart must have correct racing number on front/back and both sides. Numbers must be clearly legible by race officials

DRIVER SIGNATURE

BY SIGNING / FILLING OUT THIS FORM - I PRESENT THIS KART AND DOCUMENT TO CERTIFY THAT ALL ITEMS ON THIS FORM HAVE BEEN COMPLETED, VERIFIED, AND WILL BE MAINTAINED THROUOUT THE DURATION OF THE EVENT.

IF DRIVER IS UNDER 18, PARENT OR GUARDIAN SIGNATURE

BY SIGNING / FILLING OUT THIS FORM - I PRESENT THIS KART AND DOCUMENT TO CERTIFY THAT ALL ITEMS ON THIS FORM HAVE BEEN COMPLETED, VERIFIED, AND WILL BE MAINTAINED THROUOUT THE DURATION OF THE EVENT.